Appendix B: Overhead Crane/Hoist Inspection Checklist

Overhead Crane/Hoist Inspection Checklist (Daily or Before Each Use)				
Dept/Div:		Crane #:	Bldg. #:	Date:
Operator Name:			Life No.:	
	Locate Crane Main Disconnect Switch			
	Check Pendant Controls of Controllers or Selector: Up, Down, East, West, North, and South			
	Check Wire Rope of Chain for Damage: On main hoist and aux for worn, cut, kinked, crushed, spooling, or birdcaged cable			
	Check Hooks: Bent, spread, cracked, and safety latch			
	Check Upper Limit Switch: Hook block stop			
	Check for Reverse Reeving: Hoist cable direction			
	Check Brake System: Load, trolley, bridge, and hoist motor			
۵	Check Trolley Travel			
	Check Bridge Travel: Make sure limits and stops are in place and working. Make sure nothing is in the way of load to be lifted during travel.			
0	Check Hoist Gearing System: Any unusual noises			
0	Check Rails During Operation: Loose bolts, rail clamps, unusual wear			
	Check Lubrication: Leaks, excess grease			
0	Review Weight Limits: Scale must be used if lift weight is unknown			
	Inspect Rigging Equipment to be Utilized: Slings, shackles, rope guides, use personnel protective equipment			
0	No Defects Noted			
Note:	Personnel using BNL material handling equipment shall be a current holder of a Safety Awareness Certificate (SAC Card).			
Caution:	If any malfunction or any unusual noises, STOP using the Crane/Hoist and contact Leadman, Supervisor, or ESH Coordinator immediately.			
Use Back of The Checklist to Describe Defects This Form Shall Be Kept on File And Be Available For All Inspections				